

Energy\$averTM

Vertical Hollow Shaft Motors

NEMA Premium Efficient, rugged and reliable, the Energy \$aver VHS family is the best choice for your critical pumping applications.

	WPI	TEFC
HP	5-500	3-200
Warranty	3 year	3 year
Efficiency	Premium	Premium
Poles	4	2, 4
Speed	1800	1800, 3600
Voltage	230/460 460PWS	230/460 460PWS



Standard Features

All Cast Iron Construction
High and Extra High Thrust
Non Reverse Ratchet
Max 40°C ambient, 3,300ft altitude
Class F insulation, Class B rise
GEGARD 2400V Inverter Duty Insulation

115V Space Heater
Aegis® Shaft Grounding Ring (125HP and Above)
NC Winding Thermostats (125HP and Above)
Frame Grounding Kit (TEFC)
50 Hz Rated at 190/380V or 380V



imagination at work

Energy \$aver VHS (TEFC)

HP	RPM	Volts	Frame	FLA @ 460	Down Thrust	LRA	Nom, Eff	Cat No.	Motor List Price	Coupling List Price*	Wt. (lbs)	CD Dim. (in.)	AG Dim. (in.)
5	3600	230/460	L213TP10	12.0/6.0	1663	42	88.5	V898	\$2,395	\$265	200	18.88	23.7
5	1800	230/460	L213TP10	13.2/6.6	2071	43	89.5	V899	\$2,326	\$265	200	18.88	23.7
7.5	3600	230/460	L213TP10	18.0/9.0	1658	58	89.5	V900	\$2,434	\$265	200	18.88	23.7
7.5	1800	230/460	L213TP10	18.4/9.2	2071	61	91.7	V901	\$2,345	\$265	200	18.88	23.7
10	3600	230/460	L215TP10	23.2/11.6	1658	76	90.2	V902	\$2,637	\$265	220	18.88	23.7
10	1800	230/460	L215TP10	24.4/12.2	2065	79	91.7	V903	\$2,545	\$265	220	18.88	23.7
15	3600	230/460	L254TP10	34.6/17.3	2070	109	91	V904	\$2,957	\$324	315	23.54	28.26
15	1800	230/460	L254TP10	37.8/18.9	2570	109	92.4	V905	\$3,589	\$324	315	23.54	28.26
20	1800	230/460	L256TP10	47.6/23.8	2597	135	93	V906	\$3,955	\$324	350	23.54	28.26
25	1800	230/460	L284TP16	58.2/29.1	2976	175	93.6	V907	\$4,573	\$324	460	25.75	30.6
30	1800	230/460	L286TP16	69.4/34.11	2959	206	93.6	V908	\$4,994	\$324	510	25.75	30.6
40	1800	230/460	L324TP16	98.8/49.4	4148	298	94.1	V909	\$6,667	\$732	700	31.36	36.57
50	1800	230/460	L326TP16	123.8/61.9	4126	384	94.5	V910	\$7,617	\$732	740	31.36	36.57
60	1800	460	L364TP16	73.0	5288	435	95	V911	\$9,692	\$845	1050	35.04	40.88
75	1800	460	L365TP16	92.0	5288	530	95.4	V912	\$11,587	\$845	1050	35.04	40.88
100	1800	460	L405TP16	111.0	5086	682	95.4	V913	\$15,175	\$845	1560	39.74	46.56
125	1800	460	L444TP16	138.0	6816	891	95	V914	\$21,334	\$1,125	2050	47.37	53.54
150	1800	460	L445TP16	167.0	6816	1035	94.5	V915	\$24,941	\$1,125	2010	47.37	53.54
200	1800	460	L447TP16	218.0	11138	1384	95.4	V916	\$33,201	\$1,125	2800	55.67	62.04

Energy \$aver VHS (WPI)

HP	RPM	Volts	Frame	FLA @ 460	Down Thrust	LRA	Nom, Eff	Cat No.	Motor List Price	Coupling List Price*	Wt. (lbs)	CD Dim. (in.)	AG Dim. (in.)
5	1800	230/460	L213TP10	13.0/6.5	2092	43	91	V891	\$2,322	\$218	172	18.88	22.44
7.5	1800	230/460	L213TP10	18.6/9.3	2079	59	91	V892	\$2,408	\$218	172	18.88	22.44
10	1800	230/460	L215TP10	24.4/12.2	2071	74	91.7	V893	\$2,452	\$218	206	18.88	22.44
15	1800	230/460	L254TP10	36.0/18.0	2575	100	93	V894	\$2,478	\$229	280	23.54	26.72
20	1800	230/460	L256TP10	47.6/23.8	2575	130	93	V895	\$2,777	\$228	315	23.54	26.72
25	1800	230/460	L284TP16	58.2/29.1	2960	175	93.6	V896	\$3,193	\$234	420	23.54	29.57
30	1800	230/460	L286TP16	72.0/36.0	2960	260	94.1	V897	\$3,607	\$234	470	23.54	29.57
40	1800	230/460	L324TP16	98.8/49.4	4100	283	94.1	V881	\$4,203	\$732	700	31.36	36.93
50	1800	230/460	L326TP16	128.6/64.3	4100	410	94.5	V882	\$5,047	\$732	740	31.36	36.93
60	1800	460 PWS	L364TP16	73.4	5294	405	95	V883	\$6,162	\$732	980	35.04	40.21
75	1800	460 PWS	L365TP16	92.4	5200	516	95	V884	\$7,233	\$732	1060	35.04	40.21
100	1800	460 PWS	L404TP16	111.0	7849	681	95	V885	\$9,475	\$845	1560	39.75	45.26
125	1800	460 PWS	L405TP16	140.0	7849	785	95.4	V886	\$11,570	\$845	1590	39.75	45.26
150	1800	460 PWS	L444TP20	165.0	8225	1194	95.8	V887	\$14,095	\$1,125	2050	47.3	53.44
200	1800	460 PWS	L447TP20	218.0	8063	1319	95.8	V888	\$18,197	\$1,125	2580	55.8	61.94
250	1800	460 PWS	L447TP20	276.0	7850	1787	95.8	V889	\$22,998	\$1,125	2580	55.8	61.94
300	1800	460 PWS	L449TP20	331.0	7850	1879	95.8	V890	\$26,694	\$1,125	2610	55.8	61.94
350	1800	460 PWS	L449TP20	386.0	13345	2386	95.4	V850	\$27,759	\$1,125	2980	55.8	61.94
400	1800	460 PWS	L449TP20	438.0	13345	2511	95.4	V851	\$31,533	\$1,125	2980	55.8	61.94
400	1800	460 PWS	L449TP20	443.0	38720	2601.4	94.5	V951	\$35,733	\$1,125	2630	55.8	61.94
500	1800	460 PWS	L509TP24	549.0	14807	3285	95	V852	\$41,106	SRC ind	3570	59.9	66.32
500	1800	460 PWS	L509TP24	553.0	45304	3284.6	95	V952	\$44,453	SRC ind	3620	59.9	66.32
600	1800	460 PWS	L511TP24	646.0	44796	4009	94.5	V953	\$49,953	SRC ind	4380	67.9	74.32



imagination at work

Contact your GE sales representative for more details.

www.gepowerconversion.com

800-541-7191

"Energy \$aver" is a trademark of General Electric Company

©2014 All Rights Reserved

GEA31078 (7/14)